

Prevent Basement Flooding...

Quality & Performance. Ask for it by name.

SP Sump Pump

Sump Pump Systems

SP3000 Primary Sump Pump • SP3000-S Secondary/Stand-by Sump Pump



MODEL SP3000

Features/Advantages

- High Volume SP3000 pump, 1/2 HP. Single Phase, 115V/60HZ, 3450RPM
- Cast Aluminum Housing construction with Stainless Steel fasteners and clamps
- Thermoplastic base & impeller
- Oil filled motor for maximum heat dissipation
- PSC motor with automatic thermal overload protection
- 1 1/2" threaded discharge capable of handling up to 1/8" solids
- Complete unit is light weight, portable and compact
- Heavy duty SJTW Power cord: 10 feet long, Heavy duty with 3-prong plug
- Adjustable vertical float switch with 10 foot cord and piggy back plug
- High water alarm, 9VDC battery operated, 85 dB alarm, relay outputs for security systems
- Agency listings: CSA Approved
- Two year warranty

Product Specification

Service Requirements:

- 1/2 HP, 115V, 60Hz, single phase, 3450 RPM, 4.7 amps
- Minimum circuit breaker, 15 amps

Pumping Rates:

- 3,000 GPH @ 10' discharge
- 3,200 GPH @ 5' discharge
- Maximum head: to 26 feet

Dimensions:

- Pumping Range: 8"
- Minimum basin diameter: 12"
- Size: 8" diameter base x 12" high
- Pump weight: 11 lbs.

Model # SP3000 Primary Sump Pump

How It Works

The SP3000 is a primary sump pump systems utilizes a high capacity, commercial quality pump complete with an adjustable compact level switch. The package includes most items for a standard installation into typical sump pits. Included is a 9VDC high water alarm with relay output, suitable for connection to a home security system.

Model # SP3000-S Secondary/Stand-by Sump Pump

How It Works

The SP3000-S is a secondary, stand-by sump pump system to be used in addition to your primary main sump pump. This pump system is small in size and sits inside the sump pit next to the primary pump. The package includes most items for a standard installation into typical sump pits. The SP3000-S is a low cost redundant pump system providing protection from primary pump failure or extreme high ground water volumes.

Two Year Warranty

Materials Included

- SP3000 Sump Pump
- 1-1/2" Pipe x 12" lg. and fitting
- Check Valve, 1-1/2" Size
- Vertical Float Switch, piggyback plug
- High Water Alarm, 9V DC

Materials Included

- SP3000 Sump Pump
- 1-1/2" Pipe x 12" lg. and fitting
- Check Valve, 1-1/2" Size
- Vertical Float Switch, piggyback plug
- High Water Alarm, 9V DC
- 1-1/2" Discharge Hose x 4 Ft. long with clamps
- 2" Discharge Tee and various PVC fittings

Base Products
Corporation
Flood Prevention Products

265 Mayville Ave, Buffalo, NY 14217
Phone: 716-876-5206 Fax: 716-876-5211
Toll Free: 800-554-1426
www.basepump.com