

FLOODTEK INSTALLATION INSTRUCTIONS

Model FW

Specifications:

Voltage:	110V AC input, 6V DC output
Battery Type:	(2) 3V Lithium #CR2032
Alarm Case:	2" wide x 1-1/2" Deep x 1-3/8" high
New Battery Operational Life:	Two year standby / Five days alarming time.
Alarm:	80 decibel
Sensor Cable:	10 feet long

Installation:


- 1) Attach the product tag to the **FW** alarm cable. Write down the battery date for future reference.
- 2) Remove the cover and pull out the plastic tabs to activate the FloodTek and replace cover.
- 3) The **FW** alarm can be mounted to a wall or floor using the enclosed wood screws.
- 4) The sensor cable maybe cut to the necessary length to fit your area of protection. See below

FW Alarm



To silence the alarm or to replace the batteries, simply remove the (4) corner screws, pull cover off and press the reset button or replace the batteries, as needed.

FW Sensor



Use scissors to cut through the black mesh between the sensor tabs which are 3" apart (shown without the mesh cover for clarity). Keep the cut wires from touching each other.

Operation

Pull the clear plastic tab out to activate the alarm

- Once the sensor becomes wet the alarm will sound. Remove the sensor from the water source, dry off, and press the "Reset" button on the inside back of the alarm unit. The Floodtek is now ready for reuse. The alarm can be silenced without removing the sensor from the water by pressing the "Reset" button.
- The alarm will sound for approximately 30 seconds, then turn off for 10 seconds and repeat as long as water is present. This will extend battery life during a water detection period.

Sensor Placement

- **Residential:** Sinks, drains, toilets, sump pit, washing machine, dish washer, piping, water tanks, basement walls, AC units, ice makers, dehumidifiers, etc. **Commercial** applications: storage rooms, computer areas, warehouses, kitchens, equipment rooms, etc.

Warranty:

Base Products Corporation (The Company) warrants the FloodTek against defects in material and workmanship for a period of One Year from the date of the shipment. In the event of any defect within the warranty period, The Company will, at its option, replace or recondition the product without charge providing the product is returned, prepaid to our offices in Buffalo, New York. This shall constitute the exclusive remedy for any alleged defect. The Company shall not be responsible for any incidental, indirect, contingent, or consequential damages, including, without limitation, damages or other costs resulting from labor charges, delays, loss of use, revenue or profit, vandalism, negligence, fouling, caused by foreign material, damage from peculiar water conditions, chemicals or other circumstances over which The Company has no control. The Company makes no other warranties, express or implied, except as provided in this limited warranty. This warranty becomes void by any misapplication, misuse, abuse, or improper installation of the product. This warranty gives you specific legal rights and you may also have other rights which may vary from state to state. Warranty is applicable in the USA and Canada, only.